

ROMANDIC winter school 2026

Kranjska Gora, Slovenia, Feb. 10th 2026

Attendees' pitch presentations Tuesday



ROMANDIC

Robot Manipulation of Deformables through
Dynamic Actions

3 mins per presenter!

1	Alex	García
2	Amar	Halilovic
3	Grégory	Brivady
4	Jan	Jerićević
5	Jelena	Ćurčić
6	Luka	Šiktar
7	Marine	Petriaux
8	Michael (Michal)	Radin-Rutkowski
9	Michel	Rosselli
10	Moritz	Moosmüller
11	Nikola	Knezevic
12	Nurlan	Kabdyshev
13	Rahul	Ramachandran
14	Riccardo	Morandi
15	Sebastian	Rietsch
16	Youngbin	Yoon
17	Yuyuan	Wu

Alex García



Unifying Geometric Control and Mechanics of Elastic Rods

Àlex Garcia Herranz

Supervised by: Maria Alberich Carramiñana & Franco Coltraro


The Goal:

- Robotic manipulation of flexible objects (cables, hoses, surgical tools).

The Problem:

- **Geometric Control** (Bretl et al.): Excellent at planning complex maneuvers, but often **ignores gravity**.
- **Mechanics** (Bertails et al.): Models gravity and forces perfectly, but ignores **control**.

Our Aim: Bridge these two worlds to enable gravity-aware manipulation.



VS

Geometric Control (The Abstract)**Focus:** Geometry of $SE(3)$

- **State:** Curve $q(s) \in SE(3)$
- **Input:** Controls u_i , along generators $X_i \in \mathfrak{se}(3)$
- **Dynamics:** Costate $\mu \in \mathfrak{se}(3)^*$ related to control parameters u_1, u_2, u_3 .

$$q' = q \cdot \left(\sum_{i=1}^3 u_i X_i + X_4 \right)$$

$$\min_{q,u} \int (c_1 u_1^2 + c_2 u_2^2 + c_3 u_3^2) ds$$

Mechanics (The Physical)**Focus:** Forces & Equilibrium

- **State:** Centerline Γ , Frame \mathcal{R}
- **Input:** Strains (Curvature)
- **Equilibrium:** Force/Moment Balance

$$M' + n_0 \times T = 0$$

$$T' + p' = 0$$

Theorem: The frameworks are mathematically equivalent.

The abstract **Equation** governing the costate evolution:

$$\mu' = \text{ad}_{\frac{\delta h}{\delta \mu}}^* (\mu)$$

...is exactly the **Kirchhoff Equilibrium** equations in the local frame.

Concept	Control Theory	Mechanics	The Bridge
State	$q \in \text{SE}(3)$	Γ, \mathcal{R}	$q \equiv (\mathcal{R}, \Gamma)$
Strain	Controls u_i	Curvature k_i	$u \equiv k$
Equilibrium	Costate μ	Wrench \mathbf{T}, \mathbf{M}	$\mu \equiv (\mathcal{R}^T \mathbf{M}, \mathcal{R}^T \mathbf{T})$

-  F. Bertails-Descoubes, A. Derouet-Jourdan, V. Romero, and A. Lazarus.
Inverse design of an isotropic suspended Kirchhoff rod: theoretical and numerical results on the uniqueness of the natural shape.
Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences, 474(2212):20170837, 04 2018.
-  A. Borum and T. Bretl.
The free configuration space of a Kirchhoff elastic rod is path-connected.
In *2015 IEEE International Conference on Robotics and Automation (ICRA)*, pages 2958–2964, 2015.
-  T. Bretl and Z. McCarthy.
Quasi-static manipulation of a kirchhoff elastic rod based on a geometric analysis of equilibrium configurations.
The International Journal of Robotics Research, 33(1):48–68, 2014.

Amar Halilović



ulm university universität
uulm



Explainable Robot Navigation

Environment- and Human-Centered Approach

Amar Halilovic
Ulm University, Germany

Tuesday, 10th February 2026


Explainable Robot Navigation (XRN)

- Making robotic behavior understandable to humans
- Motivated by the rise of Explainable AI (XAI)
- Service robotics in indoor environments
- In XRN, the focus is on explaining:
 - task failures
 - plan failures
 - trajectory deviations




Research Challenges / Thesis Contributions


Environmental Explanations



Explanation Planning



Robot Explanation Identity



Thank you for your attention!

Grégory Brivady

RAINBOW

Sensor-based and interactive robotics


Design of a Capacitive Interface for Controlling the Grasp Location and Force of a Soft Gripper

Grégory BRIVADY¹, Maud MARCHAL^{1,3}, Sylvain GUÉGAN²


contact: gregory.brivady@irisa.fr

- 1: Univ. Rennes, INSA, IRISA, Rennes, France
- 2: Univ. Rennes, INSA, LGCGM, Rennes, France
- 3: Institut Universitaire de France

- **Motivation:**
 - Haptic feedback can enhance teleoperation
 - Soft robots have new capabilities thanks to their compliance...
 - ... but we need to design new interfaces and control schemes
 - In particular, want to control grasp location and force to manipulate soft objects
- **Approach:**
 - Represent the object with a deformable tangible interface
 - Mimic the grasp applied by the user with the gripper



- **Solution:**
 - 3D printed interface with embedded capacitive sensors
 - Physics-based control scheme for the gripper



Jan Jerićević

Making Learned Grasps Executable: Capability-Guided Execution for Robust Dual-Arm Cloth Unfolding

Jan Jeričević

Humanoid and Cognitive Robotics Laboratory

ROMANDIC winter school

10. 2. 2026

Kranjska Gora

Problem & Motivation

Good predicted grasps are not always executable

- Joint limits / reachability
- Collision constraints
- Low dexterity near singularities
- Approach vector constraints
- Robot dependant

Make grasp execution robust without changing the grasp predictor → robot capability





Figure 1 : Cloth unfolding as a result of unsuccessful / successful grasp



Benchmark + Prior Work (CeDiRNet-6DoF)



1. Grasp highest point

2. Grasp lowest point

3. Start observation



4. Grasp selection and execution

5. Stretching and result observation

Figure 2: ICRA 2024 Cloth Unfolding Competition - Regrasping in the air¹






Figure 3: CeDiRNet-6DoF grasp predictor²

¹V.-L. De Gusseme, et al., Manuscript submitted for publication, presented at the ICRA 2024 Cloth Competition, Yokohama, Japan, 2024

²D. Tabernik, P. Nmac, et al., "Vision-Based 6-DoF Grasp Pose Estimation for Robot Cloth Unfolding," manuscript submitted for publication, 2025"

Benchmark + Prior Work (CeDiRNet-6DoF)




1. Grasp highest point 2. Grasp lowest point 3. Start observation



4. Grasp selection and execution 5. Stretching and result observation

Figure 2: ICRA 2024 Cloth Unfolding Competition - Regrasping in the air¹



<p>Grasp success 67.5%</p>	

Figure 3: CeDiRNet-6DoF grasp predictor²

¹ V.-L. De Gusseme, et al., Manuscript submitted for publication, presented at the ICRA 2024 Cloth Competition, Yokohama, Japan, 2024

² D. Tabernik, P. Nmac, et al., "Vision-Based 6-DoF Grasp Pose Estimation for Robot Cloth Unfolding," manuscript submitted for publication, 2025"

Execution Bottleneck → Heuristic → Capability Maps

Bottleneck

- Joint limits / reachability
- Collision constraints
- Low dexterity near singularities
- Approach vector constraints
- Dual arm coupling

Cloth Pose Correction Heuristic

- Check If infeasible
- Reposition cloth (preset hold pose)
- Re-predict + re-plan

**Reduced unattempted grasps
from 9.4% to 3.6%**




Figure 4: Robot configurations in the initial, near and far cloth positions



Execution Bottleneck → Heuristic → Capability Maps

Bottleneck

- Joint limits / reachability
- Collision constraints
- Low dexterity near singularities
- Approach vector constraints
- Dual arm coupling

Cloth Pose Correction Heuristic

- Check If infeasible
- Reposition cloth (preset hold pose)
- Re-predict + re-plan

**Reduced unattempted grasps
from 9.4% to 3.6%**

Capability Maps

- Feasibility
IK+joint margins + collision-free approach
- Dexterity
Manipulability
- Task-direction dexterity
Approach vector




Figure 4: Robot configurations in the initial, near and far cloth positions




Figure 5: Left: Manipulability of a 5 DOF manipulator³.
Right: reachability of a 7 DOF manipulator⁴

³ Vahrenkamp, et al., Representing the robot's workspace through constrained manipulability analysis. *Auton Robot* 38, 2015

⁴ Quan, Y., et al., The Dexterity Capability Map for a Seven-Degree-of-Freedom Manipulator. *Machines* 2022

Execution Bottleneck → Heuristic → Capability Maps

Bottleneck

- Joint limits / reachability
- Collision constraints
- Low dexterity near singularities
- Approach vector constraints
- Dual arm coupling

Cloth Pose Correction Heuristic

- Check If infeasible
- Reposition cloth (preset hold pose)
- Re-predict + re-plan

**Reduced unattempted grasps
from 9.4% to 3.6%**

Capability Maps

- Feasibility
IK+joint margins + collision-free approach
- Dexterity
Manipulability
- Task-direction dexterity
Approach vector




Figure 4: Robot configurations in the initial, near and far cloth positions




Figure 6: Moving the grasp to a high-capability grasp region

We keep learned grasp prediction as-is and improve robustness by adapting execution using robot capability

Thank you to my
colleagues:

Peter Nmac
Domen Tabernik

Supervisor:
Prof. dr. Andrej Gams

Thank you for your attention!

Contact: jan.jericevic@ijs.si



Jelena Čurčić

An unoptimized path, finely tuned

*Jelena Ćurčić, Groschopp Systems Solutions / Faculty of Technical Sciences,
University of Novi Sad*

Hello everyone, my name is Jelena Ćurčić, and I'm a PhD student in Mechatronics, Mechatronics, Robotics, and Automation at the University of Novi Sad in Serbia. I Serbia. I work at Groschopp Systems Solutions as a Robotics Software Engineer. Engineer.





The Core of My Research

Foundations

My background sits at the intersection of **robotics, optimization, and real-world world systems.**



Mobile Robotics

I also work with **physical robots**, with my current experience mostly being with mobile, wheeled platforms.

Decision-Making Under Constraints



My recent work is centred on **decision-making and task planning for planning for autonomous robots under strict constraints**


Previous work and papers

"Evolutionary approach to Time-limited, Profit-based Traveling Salesman problem in Salesman problem in Mobile Robotics" Curcic J., Kanovic Z., Nikolic M., Savic S.

Savic S.

- Developed a solution for a modified version of the Traveling Salesman Problem (TSP) Problem (TSP)
- Introduced additional constraints such as volume capacity to reflect real-world robotics challenges
- Motivated by autonomous robot strategies for the Eurobot 2024 competition, though applicable to broader contexts like delivery and field sampling
- Modeled the problem as a global optimization task and solved it using a Genetic Algorithm (GA)
- Focused on encoding domain-specific knowledge into the initial population to accelerate convergence
- Simulated and tested different population initialization techniques and their impact on solution quality and speed





Building Autonomous Mobile Robots: Software & Control



ROS 2 Integration

Alongside optimization, I'm actively working with **ROS 2**, the Robot Operating System, which forms the backbone of advanced robotic applications.



Behaviour Trees and Simulation Software

I utilise **behaviour trees** to build sophisticated autonomous mobile robots capable of performing complex manipulation and navigation tasks. All of this was first applied to a simulated environment, specifically in IsaacSim, and later in real world.



Other fields of work

My most recent work (at work) is around the utilization of LLM models for making RAG systems. making RAG systems.

Beyond the Lab:



Basketball Player

In parallel with my academic pursuits, I'm a semi-professional basketball player, enjoying the teamwork and competitive spirit.




Eurobot Organisation

Having participated in Eurobot for three years, I'm now part of the organising the organising committee for Eurobot Serbia 2026, contributing to the next to the next generation of robotics enthusiasts.



Leisure & Socialising

With the very little free time I have left, I also enjoy watching TV series, series, reading a good book, and sharing a coffee with friends.



What I Hope to Learn

Although the robots I've worked with so far mostly interact with objects that stay exactly where you put them, I believe the work on manipulation of deformable objects is quite interesting and a missing puzzle piece in my current career-path.

"An unoptimized path, finely tuned"

Looking Forward to an Inspiring Week!


Thank You!

Luka Šiktar



fsb

cрта |



ROMANDIC presentation


Luka Šiktar

2026 | Regional Center of Excellence for Robotic Technology, University of Zagreb, Croatia



ROBOCAMP


- Complete Search and Rescue framework:
 - Hexsoon drone, RTK base, Wi-Fi router
 - Wristbands with special emergency call button and GPS module – within Wi-Fi range
 - Central computer – control room
- GPS wristband follow and CNN person follow



- GNSS (satellite) data
- Wi-Fi transmission
- Web protocols

ROBOCAMP

- CNN person follow
- GPS follow



Indoor

Outdoor

Outdoor




- GPS follow (bracelet state)




- Drone


PRONOBIS project

- Robotically navigated prostate biopsy system POC
- 7 DOF robot for automated prostate scanning and biopsy planning
- Deep-learning based prostate segmentation
- Ultrasound-only based 3D prostate reconstruction, biopsy planning and treatment execution







Workflow



Prostate phantoms

Scanning procedure

MedAP and Model



Marine Petriaux



WANDERCRAFT

Calvin : Legged robotics from
clinic to the factory floor

Let's make a robot to help people walk

Our founder's idea :
Use humanoids technology to help people walk again



From day 1, we want to build a hands-free exoskeleton, self-stabilized.

We learnt how to do autonomous locomotion while carrying uninstrumented, unmodeled, heavy loads.



Feb 2025



"Make a humanoid, you have 40 days"

10 FEB

We need arms!



End March



"40 days"

12 FEB

Parts gathering, arms assembly



**+6 DoF
+1 RGB-D camera
Same locomotion stack**



Use cases : tires and boxes and... What's next ?



Other requests

- windshields, metal sheets
- Cart pushing
- Picking/kitting

We want to build a new manipulation stack to allow:

- **Fast development** of new tasks
- **Low sim2real** gap, as contacts simulation is hard!
- **Easy demonstrations** at the client's site
- **Embodiment**-agnostic as our robot evolves quickly

Our first work in next presentation!

Michel Rosselli

A General Approach to Path Planning within C-Space Safe Corridors

Riccardo Abbati¹, Marco Riboli², Michel Rosselli², Alessandro Tasora¹ and Marco Silvestri^{1,2}



UNIVERSITÀ
DI PARMA


¹ University of Parma

SUPSI


² University of Applied Sciences
and Arts of Southern
Switzerland

Path Planning within C-Space Safe Corridors

- **Goal:** Collision-free motion from $\mathbf{x}_{\text{start}}$ to \mathbf{x}_{goal}
- **Our Proposal:** A novel geometric planner coupling **Safe Corridor** definition with **Spline-based Optimization**
- **Method:** Constructs corridors using **Overlapping Axis-Aligned Bounding Boxes (AABBs)** via a Goal-Biased exploration (GBPFC-connect)




(a)



(b)



Safe Corridor (S) Construction

- **Exploration Strategy (GBPFC-connect):**
 - Grows two foams (ξ_A, ξ_B) rooted at q_{start} and q_{goal}
- **Condition:** Terminates when foams intersect ($\xi_A \cap \xi_B \neq \emptyset$)



Safe Corridor (S) Construction


- **Exploration Strategy (GBPFC-connect):**
 - Grows two foams (ξ_A, ξ_B) rooted at q_{start} and q_{goal}
- **Condition:** Terminates when foams intersect ($\xi_A \cap \xi_B \neq \emptyset$)
- **Refinement: Shortcut & Partial Shortcut** extract the minimal overlapping subsequence S



Spline-Based Optimization

- **Goal:** Compute **Multidimensional B-Splines** inside the safe corridor
- **Method:** **LCQP** (Linearly Constrained Quadratic Programming)
- **Objective Function:**

$$\min_x f(x) = \alpha_1 f_1(x) + \alpha_2 f_2(x)$$




Spline-Based Optimization




- **Goal:** Compute **Multidimensional B-Splines** inside the safe corridor
- **Method:** **LCQP** (Linearly Constrained Quadratic Programming)
- **Objective Function:**

$$\min_x f(x) = \alpha_1 f_1(x) + \alpha_2 f_2(x)$$

- α_1 : **Reduces Geometric Acceleration** (Smoothness)
- α_2 : **Increases Distance from Obstacles** (Safety)




Results

Env.	Method	Successes ($\setminus 10$)	Path length (m)	C-space expl. CPU time (s)	Optim. CPU time (ms)
	Our ($\alpha_1=1.0, \alpha_2=0.0$)	10	1.553±0.032	3.9±2.5	10±1
	Our ($\alpha_1=0.998, \alpha_2=0.002$)	–	1.602±0.201	–	264±95
	Our ($\alpha_1=0.95, \alpha_2=0.05$)	–	1.640±0.144	–	331±54
	RRT [4] + optimisation	8	2.220±0.064	171.7±59.7	2145±587
	PRM [2] + optimisation	10	2.253±0.463	240.0±175.6	4576±1216
	RRT* [6] + optimisation	5	2.007±0.335	522.0±124.3	2588±1098
	Informed RRT* [9] + optimisation	7	1.732±0.293	438.2±196.9	2898±447
	KPIECE [42] + optimisation	5	1.857±0.514	8.8±4.4	3579±1459
	Our ($\alpha_1=1.0, \alpha_2=0.0$)	10	1.535±0.167	27.4±21.7	12±3
	Our ($\alpha_1=0.975, \alpha_2=0.025$)	–	1.625±0.282	–	205±75
	Our ($\alpha_1=0.95, \alpha_2=0.05$)	–	1.630±0.324	–	226±71
	RRT [4] + optimisation	10	1.677±0.032	121.4±81.2	3332±1901
	PRM [2] + optimisation	7	1.815±0.161	407.9±226.9	2865±279
	RRT* [6] + optimisation	4	1.757±0.124	513.8±197.9	2765±341
	Informed RRT* [9] + optimisation	7	1.754±0.058	461.7±224.6	3318±811
	KPIECE [42] + optimisation	9	1.727±0.094	108.2±98.9	2329±561
	Our ($\alpha_1=1.0, \alpha_2=0.0$)	8	2.453±0.340	56.5±24.3	16±2
	Our ($\alpha_1=0.975, \alpha_2=0.025$)	–	2.570±0.102	–	234±54
	Our ($\alpha_1=0.95, \alpha_2=0.05$)	–	2.613±0.057	–	221±45
	RRT [4] + optimisation	3	2.725±0.064	277.2±178.5	2145±587
	PRM [2] + optimisation	6	2.693±0.062	667.6±406.2	3367±1216
	RRT* [6] + optimisation	8	2.660±0.081	363.8±126.9	3265±1168
	Informed RRT* [9] + optimisation	6	2.782±0.066	582.5±128.0	1605±428
	KPIECE [42] + optimisation	6	2.932±0.232	351.9±147.6	516±458



Constrained Path

- **Goal:** Enforce **Task-Level Constraints**
(e.g., end-effector orientation)
- **Method: Manifold Projection**
 - Projects C-space configurations onto the **Task Manifold (\mathcal{M})**
 - Generates a **Manifold-Guided Safe Corridor**



References

- [1] R. Abbati, M. Riboli, M. Rosselli, A. Tasora, and M. Silvestri. A general approach to path planning within c-space safe corridors. *IEEE Robotics and Automation Letters*, 11(1):578–585, 2026
- [2] ProjectChrono. <http://projectchrono.org>. Accessed: 2026-02-01.

Questions?


Paper



Michel Rosselli

michel.rosselli@supsi.ch

Moritz Moosmüller



Humanoid Hand Design with Tactile Force Sensors



Moritz Moosmüller

Karlsruhe Institute of Technology (KIT)

Institut for Anthropomatik and Robotik (IAR)

High Performance Humanoid Technologies (H²T)


Previous developments of humanoid hands at H2T



→ Requirements for deformable object manipulation?



Requirements for deformable object manipulation

- Force sensing during grasping
- High dexterity for various grasping configurations
- → Current developments?



Developments in the design of the fingers



- Four-bar mechanism **matches** the trajectory to the **standard human grasp trajectory** [Kamper et al. 2003]
- **Underactuated:** Tendon-driven for coordinated flexion and passive extension with torsion springs.
- **Compliant fingertip** made of soft silicone with integrated (barometric) **tactile sensing**.



Hundhausen, Moosmüller et al., *GRC* (2026)

Tactile sensors

- Microcontroller in the distal finger segment reads sensor data
- Power Line Communication (PLC): Transmission of data and power via the mechanical coil springs
 - Datarate: 30 kbit/s.
 - Testing: zero failures over 500 flexion–extension cycles.




Outlook for my PhD

- Hands with underactuation → direct drive
- Torque based compliance for grasping
- Dexterity-Rating for humanoid hands



Moritz
Moosmüller



Felix
Hundhausen



Tamim
Asfour

www.humanoids.kit.edu



Thank you!



Federal Ministry
of Research, Technology
and Space

This work has been supported by the ROMANDIC-Project and the EU under grant agreement No. 101159522 , the German Federal Ministry of Research, Technology, and Space (BMFTR) under the Robotics Institute Germany (RIG).

Nikola Knežević

- Institution: **University of Belgrade**
School of Electrical Engineering
- Department: **Signals & Systems**
- Location: **Belgrade, Serbia**
- Application areas: **Industrial, Service, Healthcare**
- Research interests: **Human-Robot Collaboration, Human-centered Robotics and Mechatronics, Artificial Intelligence, Collaborative Robots, Robot Modeling and Control, Soft Robots**
- Contact: robot@etf.rs / kostaj@etf.rs, knezevic@etf.rs



PEOPLE



- **Asst. Prof. Kosta Jovanović**
- Research: **physical human-robot collaboration, cobots applications**



- **Asst. Prof. Nikola Knežević**
- Research: **human-robot collaboration, AI/ML in robotics**



- **Zaviša Gordić, PhD**
- Research: **industrial robotics, collision detection**



- **Branko Lukić, PhD**
- Research: **VSA, stiffness control, robot control**



- **Maja Trumić, PhD**
- Research: **soft robots, robot control**




- **Filip Bečanović, PhD**
- Research: **human motion analysis, inverse optimal control**



- **Miloš Petrović**
PhD student
- Research: **human motion analysis, ergonomics, MoCap**



- **Gorana Milovanović,**
PhD student
- Research: **Human-machine interfaces**



- **Nikola Ružić,**
PhD student
- Research: **ROS, Mobile manipulators**



- **Veljko Todić,**
PhD student
- Research: **human-robot interaction in XR**



- **Anastasija Rakic,**
PhD student
- Research: **inverse RL**

LABORATORY



cooperative industrial robot cell
(by ABB, Denso and Siemens)



industrial SCARA robot
(by FANUC)



mobile cobot
(Franka Research III on
Robotnik omniwheel base)



qb robotics®

VSA actuators



AI-powered cobot
with integrated
vision - MAiRA



reconfigurable
soft grippers



F/T sensors




sensors for biomechanics



Franka Emika Panda



ABB YuMi




Soft robotics –
lab prototypes

RESEARCH


Research challenges:

- 1) **Development and control of new actuators**
compliant (VSA/antagonistic), bio-inspired
- 2) **Human motion and behavior pattern analysis and prediction**
based on MOCAP + wearables sensors (EMG, EEG, IMU)
more efficient pHRI and improved human ergonomics
- 3) **New methods for assesment of safe and efficient pHRI**
with minimal set of sensors – based on signal processing and control
theory
- 4) **New robot control methods for safe and efficient pHRI**
mechanical impedance shapping and control





A Geometric Approach to Task-Specific Cartesian Stiffness Shaping

- **Methods for shaping Cartesian stiffness matrix of a robot** singular decomposition of the stiffness matrix, optimal exploitation of the stiffness space and joint positions, nonlinear sequential least square programming optimization



$$K_C = (J(q)K_j^{-1}J(q)^T)^{-1}$$

$$K_C = U\Lambda U^{-1}$$



A Geometric Approach to Task-Specific Cartesian Stiffness Shaping




KJ N. Knezevic, B. Lukic, T. Petric
Journal of Intelligent & Robotic Systems 110 (14), 1-11

[Online cartesian compliance shaping of redundant robots in assembly tasks](#)

B Lukić, K Jovanović, L Žiljapah, T Petrić
Machines 11 (1), 35



GCSS algorithm mode – No disturbance





Neuroergonomic Workstation for Human-Centered Cobot-Supported Manual Assembly Process

Assembling different products with specific models in low batches requires a high level of worker attention and engagement making the manufacturing laborious.

The objective of the BrainWatch is to increase the productivity of such processes while improving workers' satisfaction by human-centred modular neuroergonomic workcell:


- Module 1: physical assistance (**Cobot**)
- Module 2: audio-visual assistance (**ADIN** – adaptive GUI),
- Module 3: physical assessment (**M2O2P-L** – non-invasive HMI)
- Module 4: non-physical (cognitive) assessment (**BrainWatch**),
- Module 5: strategic support (expert system - **FLINT**).

Toward Industry 5.0: A Neuroergonomic Workstation for a Human-Centered, Collaborative Robot-Supported Manual Assembly Process
N Knežević, A Savić, Z Gordić, A Ajoudani, K Jovanović
IEEE Robotics & Automation Magazine



Neuroergonomic Workstation for Human-Centered Cobot-Supported Manual Assembly Process

BrainWatch 2.0 – Cobot + XR headset



CONTACT



Thank you for your attention!



- **Asst. Prof. Nikola Knežević**
- Research: **human-robot collaboration, AI/ML in robotics**

website: <http://robot.etf.rs/>

e-mail: robot@etf.rs, knezevic@etf.rs

Nurlan Kabdyshev



Active Tactile Exploration for Object Understanding in Robotic Manipulation

Nurlan Kabdyshev

CITIUS, University of Santiago de Compostela (Spain) and Institut
Pascal, Clermont Auvergne INP (France).



Supervisors: Juan Antonio Corrales Ramon;
Youcef Mezouar

Experiment Setup



Preliminary Results

Color-coded tactile measurements projected onto a reconstructed surface band from bilateral contact.



Acknowledgements

N. Kabdyshev was funded by the Spanish Ministry of Science, Innovation and Universities (Ref. MICIU/AEI/10.13039/501100011033) through the research project FedeMINDex (Ref. CNS2024-154907), by the Interreg VI-B SUDOE Programme through the research project ROBOTA-SUDOE (Ref. S1/1.1/P0125), by ANR-25-PERO-0003 PEPR Robotique France 2030 - PC DRMI (Dexterous Robotic Manipulation for Industry), and by the European Union (European Regional Development Fund - ERDF).



Rahul Ramachandran



ROMANDIC

THE NATIONAL ROBOTARIUM

PEOPLE CENTRED :: INTELLIGENCE DRIVEN

Introduction and Recent Work

Presentation By,

*Rahul R. Ramachandran
Robotics Engineer
Manipulation Team Lead
The National Robotarium (UK)*

r.ramachandran@hw.ac.uk

About Me

Education and Experience:

B.Tech in Mechatronics engineering (First Class) from SRM, India
Visiting Research Student, Tokai University, Japan
MSc by Research (MRes) in Robotics (Distinction) from BRL, UK
I had worked in different areas of robotics namely, Marine Robotics, Aerial robotics, Continuum robotics, and Human-Robot interaction (HRI)
5+ years of Industry experience - 2 years in the Aerospace/Defense Industry and 3.6 years with The National Robotarium so far

Hobbies:

I like reading murder-mystery novels, traveling, playing snooker/pool and Badminton.

Experience:

- Robotic system design
- Planning and Control
- Robot vision-based navigation
- Robotic Simulation

Skills Summary:

- Language: Python, C++, LabVIEW, MATLAB
- Softwares: ROS1, ROS2, Isaac Sim, Fusion360



The National Robotarium's Physical Presence



Incubation & Colocation

- Office Space
- Events, Meetings & Seminars
- Hot-Desks
- Workshop



Talent & Skills

- Schools
- Colleges
- Continuing Professional Development (CPD)
- Public Engagement



Test Facilities

- Wave Tank
- Outdoor Test Area
- RAS Lab
- Living Labs



People

- Robot Systems Engineers
- Academics
- Researchers
- Robot Technicians
- Project Managers
- Students



Lab Space

- Robotics & Autonomous Systems (RAS)
- Human-Robot Interaction
- Lasers
- Outdoor Test Area
- User Defined



Robots

Spot	UAVs
Husky	Flash
Pepper	FurHat
iCub	TIAGo
Nao	...and more

The National Robotarium's Reach



Industry

- Energy
- Healthcare
- Construction
- Hospitality
- Agriculture
- Space
- Manufacturing



Health & Social Care

- NHS
- Private
- Social Housing



Universities

- Research
- Teaching



Robotic Centres

- UK
- Global



Finance

- Private
- Public



Global Reach

- UK
- Dubai
- Malaysia



THE NATIONAL
ROBOTARIUM
PEOPLE CENTRED :: INTELLIGENCE DRIVEN


NR Manipulation Focus Group Demo 1

About the Demo:

Pick and Place using ROS 2 and Isaac Sim



This project demonstrates vision-based pick-and-place of objects using Aruco tags to identify and differentiate objects for sorting. The demo is implemented on the Ufactory xArm5 robot and uses an Intel RealSense D435i depth camera.

A digital twin of The National Robotarium (NR) RAS lab cobot stations was created in NVIDIA Isaac Sim, and the software is implemented using ROS 2, MoveIt2, and NVIDIA Isaac Sim Omnigraph.




Demo 1 Implementation framework

- xArm ROS 2 developer packages from Ufactory
- Nvidia Isaac Sim OmniGraph for simulation (SITL)
- OnShape for robot design
- High-fidelity simulation
- ROS 2 ecosystem integration
- Synthetic data generation
- Digital twin potential
- Scalable experiments



Looking to Collaborate


1. Benchmarking efforts in collaboration with COMPARE group - Open-Source Ecosystem for Robotic Manipulation.
2. Collaboration with University research groups looking into robot testing and validation using digital twin but not limited to.
3. Anyone from Industry looking for facilities such as ours and looking for testing and validation support.



Thank You

Looking to Collaborate, let's connect

The National
Robotarium



Rahul R.
Ramachandran



THE NATIONAL
ROBOTARIUM
PEOPLE CENTRED :: INTELLIGENCE DRIVEN



THE UNIVERSITY *of* EDINBURGH

Riccardo Morandi

Lagrangian Model Order Reduction of Deformable Objects Dynamics

Riccardo Morandi

ROMANDIC Winter School
Kranjska Gora, February 2026

Riccardo Morandi

PhD student since October 2025

Research Interest

- **Robot learning and control**
- **Physics and differential geometry as inductive biases**
- **theoretically grounded and data-efficient** methods
- Application to **deformable object manipulation**

Supervisor:


Prof. Noémie Jaquier

Group:

Geometric Robot Learning Lab



KTH – Dept. of Robotics, Perception and Learning



Deformations as Points on a Fréchet Manifold

In continuum mechanics, the system has infinitely many degrees of freedom. Instead of discrete coordinates, the configuration is a **deformation of a body**.

Each deformation can be represented as an **embedding**:


$$\phi : \mathcal{B} \rightarrow \mathcal{A}$$

Therefore, the configuration manifold is the infinite dimensional Fréchet manifold of embeddings:

$$\mathcal{Q} = Emb(\mathcal{B}, \mathcal{A})$$

The **Lagrangian functional** is an integral over the body:

$$\mathcal{L} : (\phi, v) \mapsto \frac{1}{2} \int_{\mathcal{B}} \rho_0 \|v\|^2 - \left[\int_{\mathcal{B}} \rho_0 e(\nabla_X \phi) + \int_{\mathcal{B}} \rho_0 \mathbf{g} \cdot \phi \right]$$




W. Noll. A new mathematical theory of simple materials. Archive for Rational Mechanics and Analysis. 1972.
 Masrden J. E. and Hughes T. J.R. Mathematical Foundations of Elasticity. Dover. 1994.
 B. Kolev and R. Desmorat. An intrinsic geometric formulation of hyper-elasticity, pressure potential and non-holonomic constraints. Journal of Elasticity. 2021.

Model Order Reduction as Embedded sub-Manifold

In practice, we try to **learn a surrogate dynamical system** and its parameters that preserves the original Lagrangian structure via a structure-preserving MOR.

Leveraging the geometric setting, we consider the reduced system to be a **d-dimensional embedded sub-manifold** of the configuration manifold.



This framework turns continuum mechanics PDEs into a **finite dimensional ODE** which can be treated with classical tools, while preserving the geometry and physics of the configuration manifold.

$$\rho_0 \partial_{tt} \phi = \nabla_X \cdot \left(\frac{\partial W}{\partial F} (\nabla_X \phi) \right) + \rho_0 b$$

$$\updownarrow$$

$$\tilde{M}(\tilde{q}) \ddot{\tilde{q}} + c(\tilde{q}, \dot{\tilde{q}}) \dot{\tilde{q}} + g(\tilde{q}) = \tilde{r}(\tilde{q})$$

Sebastian Rietsch

Combining Visual Imitation Learning and Reinforcement Learning for Robotic Manipulation

Sebastian Rietsch

Karlsruhe Institute of Technology (KIT)



Motivation

- Imitation learning is showing promising results, but robot demonstrations are **expensive and hard to acquire**
 - Especially true for dexterous hands and deformables
- Visual human demonstrations, on the other hand, are **intuitive and cheap**, but lack concrete action labels and suffer from an embodiment gap between human and robot




- ▶ Leverage reinforcement learning to bridge the gap




Sparse geometric constraints for reinforcement learning

- Given a small set of human demonstrations, extract a task representation that generalizes to object instances of objects of the same category
- Translate into a reinforcement learning problem where the reward function gives
 - **Weak guidance** on where to manipulate
 - **Strong guidance** on what to imitate
- Emphasis on training of **non-demonstrated objects**




Visual demonstration

Keypoint-based geometric constraints





Keypoint correspondence



Dense reward formulation

Pitch for ROMANDIC?

- ▶ Instead of falling for the behavioral cloning trap





Sebastian
Rietsch



Jianfeng
Gao



Tamim
Asfour

www.humanoids.kit.edu



Thank you!

Youngbin Yoon



A Human Demonstration Dataset for Analyzing Topological Changes in Knot Tying

Youngbin Yoon

My research




Knot tying

- Study how to transform a current knot state into a desired knot configuration
- Enable robots to tie knots through human demonstrations



My research

Knot tying



Yuyuan Wu

Multimodal Teleoperation and Imitation Learning

Yuyuan Wu



ROMANDIC





IDLab
INTERNET & DATA LAB

Contact: Yuyuan.Wu@UGent.be

Multimodal Teleoperation and Imitation Learning

- Intuitive 6-DoF (Torque) control
- Scalable to diverse hardware configurations
- Real-time feedback of multi-modal data (visual, haptic, auditory) within an immersive UI
- High-quality demonstration collection



ROMANDIC



IDLab
INTERNET & DATA LAB

Contact: Yuyuan.Wu@UGent.be

Multimodal Teleoperation and Imitation Learning



Tactile Sensor Development



- Sensing: High-Density Magnetic Tactile Matrix
- Control: Compliant Torque-level Framework (UR Series)
- Learning: Tactile-Driven Imitation Learning



ROMANDIC




IDLab
INTERNET & DATA LAB

Contact: Yuyuan.Wu@UGent.be

ROMANDIC winter school is supported by

PAL

ABB



FRANKA ROBOTICS



Grant agreement ID: 101070596



Funded by
the European Union

Project ROMANDIC Grant agreement ID: 101159522



ROMANDIC



JSI



CSIC

CONSEJO SUPERIOR DE INVESTIGACIONES CIENTÍFICAS



Karlsruher Institut für Technologie

Funded by the European Union. Views and opinions expressed are however those of the author only and do not necessarily reflect those of the European Union or European Research Executive Agency (REA). Neither the European Union nor the granting authority can be held responsible for them.